

Code & product name: 959999 PLYCEM SLOTTED BOARD TABLLA 8mm 1219x2438mm A11 D76, 960000 PLYCEM SLOTTED BOARD TABLLA JS 8mm 1219x2438mm A11 D76

Description: Plycem Slotted is a grooved board that allows to give a wooden slats appearance in the application of ceilings, walls and eaves.

Installation aspects can be consulted at www.plycem.com in the Plycem Slotted Board Installation Guide.

Manufacture and Quality Control

Plycem panels are manufactured at facilities certified with the ISO 9001:2015, ISO 14001:2015 and ISO 45001: 2018 standards. Plycem Slotted Boards are Type A, Grade in accordance with the ASTM C 1186-08 standard and Category A Class 1 Level 1 in accordance with the INTE/ISO 8336:2018. The product complies with Costa Rican Technical Regulation RTCR 491:2017

Product Components

Portland cement, calcium carbonate, cellulose fibers, and other minor aggregates. They comply with the resistance, safety, and durability requirements and with the most demanding environmental regulations.

Technical Specifications

Description	Minimum Value	Maximum Value
Flexural Strength (in equilibrium)(N/mm ²) (ASTM C 1186)	7.0	
Flexion elastic module (saturated) (kN/mm ²) (ISO 8336/ASTM C 1186)	1.0	3.0
Density (kg/dm ³) (ISO 8336)	1.08	1.18
Moisture (%) (Own process)	0.0	8.0
Total water absorption (%) (ISO 8336)		40
Superficial absorption Cobb(%) (Own process)		25
Moisture Movement (%)		0.13
Total shrinkage (mm/m) (Own process)		3.5
Water absorption (Karsten)(ml/24h) Exposed side (Own process)		6.0
Smoke development (ASTM E-84)		0
Flame spread (ASTM E-84)		0

Physical characteristics

Nominal Measurements

Measurement	Size (mm)	Tolerance (mm)
Thickness	8.0	±0.6
Useful width	1219	±2.0
Length	2438	±2.0

Weight and coverage	
Weight (kg/un)	27.15
Useful coverage (m ²)	2.97

Ask for minimum production quantity and available stock.



Certifications

PLYCEM Construsistemas Costa Rica S.A.



PLYCEM Construsistemas El Salvador S.A.



Warranty inquiries on www.plycem.com

This information is the property of Plycem and must not be reproduced in whole or in part without the owner's consent.
Release Date: January 2023

Code & product name: 960080 PLYCEM SLOTTED BOARD TABLLA 11mm 1229x2438mm A11 D76, 960082 PLYCEM SLOTTED BOARD TABLLA JS 11mm 1229x2438mm

Description: Plycem Slotted is a grooved board that allows to give a wooden slats appearance in the application of ceilings, walls and eaves.

Installation aspects can be consulted at www.plycem.com in the Plycem Slotted Board Installation Guide.

Manufacture and Quality Control

Plycem panels are manufactured at facilities certified with the ISO 9001:2015, ISO 14001:2015 and ISO 45001: 2018 standards. Plycem Slotted Boards are Type A, Grade in accordance with the ASTM C 1186-08 standard and Category A Class 1 Level 1 in accordance with the INTE/ISO 8336:2018. The product complies with Costa Rican Technical Regulation RTCR 491:2017

Product Components

Portland cement, calcium carbonate, cellulose fibers, and other minor aggregates. They comply with the resistance, safety, and durability requirements and with the most demanding environmental regulations.

Technical Specifications

Description	Minimum Value	Maximum Value
Flexural Strength (in equilibrium)(N/mm ²) (ASTM C 1186)	7.0	
Flexion elastic module (saturated) (kN/mm ²) (ISO 8336/ASTM C 1186)	1.0	3.0
Density (kg/dm ³) (ISO 8336)	1.08	1.18
Moisture (%) (Own process)	0.0	8.0
Total water absorption (%) (ISO 8336)		40
Superficial absorption Cobb(%) (Own process)		25
Moisture Movement (%)		0.13
Total shrinkage (mm/m) (Own process)		3.5
Water absorption (Karsten)(ml/24h) Exposed side (Own process)		6.0
Smoke development (ASTM E-84)		0
Flame spread (ASTM E-84)		0


Physical characteristics

Nominal Measurements


Measurement	Size (mm)	Tolerance (mm)
Thickness	11.0	±0.6
Useful width	1219	±2.0
Length	2438	±2.0

Weight and coverage	
Weight (kg/un)	37.33
Useful coverage (m ²)	2.97


Ask for minimum production quantity and available stock.



TABLILLA



TABLILLA JS



CAMPESTRE



MEDITERRANEO

Certifications

PLYCEM Construsistemas Costa Rica S.A.



PLYCEM Construsistemas El Salvador S.A.



Warranty inquiries on www.plycem.com

This information is the property of Plycem and must not be reproduced in whole or in part without the owner's consent.
Release Date: January 2023

Code & product name: 960117 PLYCEM SLOTTED BOARD MDTNO 14mm 1229x2438mm A11 D141, 964746 PLYCEM SLOTTED BOARD TABLLA JS 14mm 1229x3050mm A11 D76

Description: Plycem Slotted is a grooved board that allows to give a wooden slats appearance in the application of ceilings, walls and eaves.

Installation aspects can be consulted at www.plycem.com in the Plycem Slotted Board Installation Guide.

Manufacture and Quality Control

Plycem panels are manufactured at facilities certified with the ISO 9001:2015, ISO 14001:2015 and ISO 45001: 2018 standards. Plycem Slotted Boards are Type A, Grade in accordance with the ASTM C 1186-08 standard and Category A Class 1 Level 1 in accordance with the INTE/ISO 8336:2018. The product complies with Costa Rican Technical Regulation RTCR 491:2017

Product Components

Portland cement, calcium carbonate, cellulose fibers, and other minor aggregates. They comply with the resistance, safety, and durability requirements and with the most demanding environmental regulations.

Technical Specifications

Description	Minimum Value	Maximum Value
Flexural Strength (in equilibrium)(N/mm ²) (ASTM C 1186)	7.0	
Flexion elastic module (saturated) (kN/mm ²) (ISO 8336/ASTM C 1186)	1.0	3.0
Density (kg/dm ³) (ISO 8336)	1.08	1.18
Moisture (%) (Own process)	0.0	8.0
Total water absorption (%) (ISO 8336)		40
Superficial absorption Cobb(%) (Own process)		25
Moisture Movement (%)		0.13
Total shrinkage (mm/m) (Own process)		3.5
Water absorption (Karsten)(ml/24h) Exposed side (Own process)		6.0
Smoke development (ASTM E-84)		0
Flame spread (ASTM E-84)		0

Physical characteristics

Nominal Measurements

Measurement	Size (mm)	Tolerance (mm)
Thickness	14.0	±0.6
Useful width	1219	±2.0
Length	2438	±2.0
	3050	
Weight and coverage		
Weight (kg/un)	37.33	
Useful coverage (m ²)	2.97	

Ask for minimum production quantity and available stock.




TABLILLA



TABLILLA JS



CAMPESTRE



MEDITERRANEO

Certifications

PLYCEM Construsistemas Costa Rica S.A.



PLYCEM Construsistemas El Salvador S.A.



Warranty inquiries on www.plycem.com

This information is the property of Plycem and must not be reproduced in whole or in part without the owner's consent.
Release Date: January 2023

Code & product name: 9960121 PLYCEM SLOTTED BOARD TABLLA JS 17mm 1229x2438mm A11 D76.

Description: Plycem Slotted is a grooved board that allows to give a wooden slats appearance in the application of ceilings, walls and eaves.

Installation aspects can be consulted at www.plycem.com in the Plycem Slotted Board Installation Guide.

Manufacture and Quality Control

Plycem panels are manufactured at facilities certified with the ISO 9001:2015, ISO 14001:2015 and ISO 45001: 2018 standards. Plycem Slotted Boards are Type A, Grade in accordance with the ASTM C 1186-08 standard and Category A Class 1 Level 1 in accordance with the INTE/ISO 8336:2018. The product complies with Costa Rican Technical Regulation RTCR 491:2017

Product Components

Portland cement, calcium carbonate, cellulose fibers, and other minor aggregates. They comply with the resistance, safety, and durability requirements and with the most demanding environmental regulations.

Technical Specifications

Description	Minimum Value	Maximum Value
Flexural Strength (in equilibrium)(N/mm ²) (ASTM C 1186)	7.0	
Flexion elastic module (saturated) (kN/mm ²) (ISO 8336/ASTM C 1186)	1.0	3.0
Density (kg/dm ³) (ISO 8336)	1.08	1.18
Moisture (%) (Own process)	0.0	8.0
Total water absorption (%) (ISO 8336)		40
Superficial absorption Cobb(%) (Own process)		25
Moisture Movement (%)		0.13
Total shrinkage (mm/m) (Own process)		3.5
Water absorption (Karsten)(ml/24h) Exposed side (Own process)		6.0
Smoke development (ASTM E-84)		0
Flame spread (ASTM E-84)		0

Physical characteristics

Nominal Measurements

Measurement	Size (mm)	Tolerance (mm)
Thickness	17.0	±0.6
Useful width	1219	±2.0
Length	2438	±2.0

Weight and coverage	
Weight (kg/un)	57.70
Useful coverage (m ²)	2.97

Ask for minimum production quantity and available stock.



Certifications

PLYCEM Construsistemas Costa Rica S.A.



PLYCEM Construsistemas El Salvador S.A.



Warranty inquiries on www.plycem.com

This information is the property of Plycem and must not be reproduced in whole or in part without the owner's consent.

Release Date: January 2023