

Code & product name: 73672TINACO PE EUREKA AZUL 250LTS (AN), 1314475 TINACO PE EUREKA AZUL 450 LTS (AN), 1314474 TINACO PE EUREKA AZUL 750 LTS (AN), 1314530 TINACO PE EUREKA AZUL 1100 LTS (AN), 1314473 TINACO PE EUREKA AZUL 2,500 LTS (AN), 948166 TINACO PE EUREKA ARENA 450 L, 948039 TINACO PE EUREKA ARENA 750 L, 947964 TINACO PE EUREKA ARENA 1,100 L, 947664 TINACO PE EUREKA ARENA 2,500 L, 1315104 TINACO PE EUREKA ARENA AMC 450 L, 1315102 TINACO PE EUREKA ARENA AMC 750 L, 1315100 TINACO PE EUREKA ARENA AMC 1,100 L, 1315098 TINACO PE EUREKA ARENA AMC 2,500 L, 142780 TANQUE C/TAPA EUREKA TRICAPA ARENA 450 LTS, 142781 TANQUE C/TAPA EUREKA TRICAPA ARENA 750 LTS, 142782 TANQUE C/TAPA EUREKA TRICAPA ARENA 1,100 LTS, 142800 TANQUE C/TAPA EUREKA TRICAPA ARENA 2500 LTS

Description: Plycem Eureka Tanks are manufactured using the most advanced technology in rotomolding, using polyethylene resins of the highest quality, which provides great strength, lightness and durability, maintaining unchanged the physical properties of the stored water.

Plycem Eureka Tanks provide high resistance due to their characteristic reinforcement belts and are offered in two presentations; Two layer or three-layer that provides better protection, durability and aesthetics. Plycem Eureka Tanks are easy and quick to install, avoiding the high masonry costs required for a traditional tank. They are also the only ones in the market that offer a 100-year warranty. Installation aspects can be consulted at www.plycem.com in Plycem Eureka Tank Installation Guide.

MANUFACTURE AND QUALITY CONTROL

Plycem Eureka Tanks are manufactured in ISO 9001:2015, ISO 14001:2015 and ISO 45001:2018 certified manufacturing sites.

CHARACTERISTICS

- Internal layer of foamed polyethylene provides thermal insulation. This layer is smooth, preventing particles in suspension from adhering. The white color in the three-layer tanks allows the water quality to be seen.
- With sand, blue or black outer coating prevents penetration of UV rays and sunlight (prevents algae).
- Intermediate layer (three-layer) resists UV radiation and protects against solar rays (prevents algae and microorganisms).
- Click-on lid seals the tank and makes it easy to close or remove the lid.
- The flange, cover and ring are replaceable as well as the filter and other components.
- Reinforcement belts and structured bottom to avoid deformation of the walls and floor.

CERTIFICATIONS


PLYCEM Construsistemas Costa Rica S.A.



PLYCEM Construsistemas El Salvador S.A.



MEASUREMENTS



Ask for available of stock

Capacity liters	A mm	B mm	People	Weight Three-layer (kg)	Weight Two-layer(Blue) (kg)
250	875	570	1-2	-	7
450	905	865	2	11	9
750	1100	1130	4	15	11
1100	1160	1265	5	19	14.5
2500	1610	1540	10	41	29

COMPLEMENTARY ACCESSORIES



Note:

*Ask for the accessories kit content. Filter may be included or optional depending on country. The type of filter will depend on inventory availability